




TECHNICAL DATASHEET

Printed: 04/11/2021
Product Management
Transportation Europe

Central Article Code: L02067C69-C Created: 30/01/2014 ETN Code or Other: Modified: 01/09/2021







Final Outlook L0269-C Approval date 15/02/2014

PERFORMANCES

Voltage (V): 12 V

C20 (Ah): 60.0 20 h

Rc (min): 0

Cranking (A): 640 EN

Vibration: Manufactured Specific
Endurance: VW Requirement (MHF)

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

CONTAINER

Type: L02 BLACK

Hold Down: B13

H.D. Adapter: No

COVER

Type: Double with Integrated BLACK

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No SOCI: No Ventilation: Central

Filter: 1 Filter at Left

Lateral Plug: No

WEIGHT AND STD. DIMENSIONS

Battery Weight (kg \pm 5%): 17.0 Volume acid (l \pm 5%): 3.3 Length (mm \pm 2): 242

Width (mm ± 2): 175 Height (mm ± 2): 190

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

PLUGS

Type: 1 x Vent Sealed PSL-OE BLACK

HANDLES

Type: 1 x PSL OE Integrated BLACK

OTHERS

Degassing Tube: No